


Flexbox
CSCI 3720

East Tennessee State University
Department of Computing




CSCI 3720
Intermediate Web Design

1

CSS3 Flexbox

Flexible boxes, or flexbox, is a new layout mode in CSS3
Use of flexbox ensures that elements behave predictably when the page layout must accommodate different screen sizes and different display devices
For many applications, the flexible box model provides an improvement over the block model in that it does not use floats, nor do the flex container's margins collapse with the margins of its contents

East Tennessee State University
Department of Computing



CSCI 3720
Intermediate Web Design

2


CSS3 Flexbox - Concepts

Flexbox consists of flex containers and flex items

A flex container is declared by setting the display property of an element to either flex (rendered as a block) or inline-flex (rendered as inline)

Inside a flex container there is one or more flex items

East Tennessee State University
Department of Computing



CSCI 3720
Intermediate Web Design

3

CSS3 Flexbox - Concepts


Note: Everything outside a flex container and inside a flex item is rendered as usual

Flexbox defines how flex items are laid out inside a flex container

Flex items are positioned inside a flex container along a flex line

By default there is only one flex line per flex container


East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

4

CSS3 Flexbox - Concepts




Cross Axis

Main Axis

Flex Container


East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

5

CSS3 Flexbox - Concepts



Cross Axis

Main Axis


Flex Container

Flex Item

Flex Item

Flex Item

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

6

CSS3 Flexbox - Code

CSS:

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

.flex-item {
  background-color: cornflowerblue;
  width: 100px;
  height: 100px;
  margin: 10px;
}

```

Why do we need this?

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

7

CSS3 Flexbox - Code

HTML:

```

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

8

CSS3 Flexbox - Code

Result:

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

9

CSS3 Flexbox - Code

It is also possible to change the direction of the flex line

If we set the direction property to rtl (right-to-left), the text is drawn right to left, and also the flex line changes direction, which will change the page layout

```


body {
  direction: rtl;
}

.flex-container {
  display: -webkit-flex;
  display: flex;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

.flex-item {
  background-color: cornflowerblue;
  width: 100px;
  height: 100px;
  margin: 10px;
}

```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design

10




CSS3 Flexbox - Code

Result:



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

11




CSS3 Flexbox - Flex Direction

The flex-direction property specifies the direction of the flexible items inside the flex container. The default value of flex-direction is row (left-to-right, top-to-bottom)

The other values are as follows:

- row-reverse** - If the writing-mode (direction) is left to right, the flex items will be laid out right to left
- column** - If the writing system is horizontal, the flex items will be laid out vertically
- column-reverse** - Same as column, but reversed

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

12



CSS3 Flexbox - Flex Direction

Example:
(Row-reverse)


```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-flex-direction: row-reverse;
  flex-direction: row-reverse;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 3720
Intermediate Web Design


13

CSS3 Flexbox - Flex Direction

Example:



East Tennessee State University
Department of Computing



CSCI 3720
Intermediate Web Design

14

CSS3 Flexbox - Flex Direction

Example:
(Column)


```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-flex-direction: column;
  flex-direction: column;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 3720
Intermediate Web Design


15

CSS3 Flexbox - Flex Direction

Example:



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

16

CSS3 Flexbox - Flex Direction


Example:
(Column-reverse)

```

.flex-container {
  display: webkit-flex;
  display: flex;
  webkit-flex-direction: column-reverse;
  flex-direction: column-reverse;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


17

CSS3 Flexbox - Flex Direction

Example:



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

18

justify-content Property

The `justify-content` property horizontally aligns the flexible container's items when the items do not use all available space on the main-axis

The possible values are as follows:

- `flex-start` - Default value. Items are positioned at the beginning of the container
- `flex-end` - Items are positioned at the end of the container
- `center` - Items are positioned at the center of the container
- `space-between` - Items are positioned with space between the lines
- `space-around` - Items are positioned with space before, between, and after the lines

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

19

justify-content Property

Example:
(Flex-end)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-justify-content: flex-end;
  justify-content: flex-end;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
    
```

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

20

justify-content Property

Example
(Flex-end):

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

21

justify-content Property

Example: (center)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-justify-content: center;
  justify-content: center;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
    
```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


22

justify-content Property

Example: (center)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

23

justify-content Property


Example: (space-between)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-justify-content: space-between;
  justify-content: space-between;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
    
```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


24

justify-content Property

Example:
(space-between)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

25


align-items Property

The **align-items** property vertically aligns the flexible container's items when the items do not use all available space on the cross-axis

The possible values are as follows:

- stretch** - Default value. Items are stretched to fit the container
- flex-start** - Items are positioned at the top of the container
- flex-end** - Items are positioned at the bottom of the container
- center** - Items are positioned at the center of the container (vertically)
- baseline** - Items are positioned at the baseline of the container

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

26

align-items Property


Example:
(Stretch)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-align-items: stretch;
  align-items: stretch;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


27

`align-items` Property

Example:
(Stretch)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

28

`align-items` Property

Example:
(Flex-start)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-align-items: flex-start;
  align-items: flex-start;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
    
```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


29

`align-items` Property

Example:
(Flex-start)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

30

align-items Property

Example:
(Flex-end)

```
.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-align-items: flex-end;
  align-items: flex-end;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}


<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
```



31



align-items Property

Example:
(Flex-end)

32



align-items Property

Example:
(Center)

```
.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-align-items: center;
  align-items: center;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>
```




33



`align-items` Property

Example:
(Center)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

34

`align-items` Property

Example:
(Baseline)


```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-align-items: baseline;
  align-items: baseline;
  width: 400px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

35

`align-items` Property

Example:
(Baseline)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

36


flex-wrap Property

The flex-wrap property specifies whether the flex items should wrap or not, if there is not enough room for them on one flex line

The possible values are as follows:

- nowrap** - Default value. The flexible items will not wrap
- wrap** - The flexible items will wrap if necessary
- wrap-reverse** - The flexible items will wrap, if necessary, in reverse order

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

37

flex-wrap Property

Example: (Nowrap)

```

.flex-container {
  display: webkit-flex;
  display: flex;
  -webkit-flex-wrap: nowrap;
  flex-wrap: nowrap;
  width: 300px;
  height: 250px;
  background-color: lightgrey;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design


38

flex-wrap Property

Example: (Nowrap)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

39

flex-wrap Property

Example: (Wrap)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-flex-wrap: wrap;
  flex-wrap: wrap;
  width: 300px;
  height: 250px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


40

flex-wrap Property

Example: (wrap)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

41


align-content Property

The align-content property modifies the behavior of the flex-wrap property. It is similar to align-items, but instead of aligning flex items, it aligns flex lines

The possible values are as follows:

- stretch - Default value. Lines stretch to take up the remaining space
- flex-start - Lines are packed toward the start of the flex container
- flex-end - Lines are packed toward the end of the flex container

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

42

align-content Property

The align-content property modifies the behavior of the flex-wrap property. It is similar to align-items, but instead of aligning flex items, it aligns flex lines

The possible values are as follows:

- center** - Lines are packed toward the center of the flex container
- space-between** - Lines are evenly distributed in the flex container
- space-around** - Lines are evenly distributed in the flex container, with half-size spaces on either end

43

align-content Property

Example:
(Center)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-flex-wrap: wrap;
  flex-wrap: wrap;
  -webkit-align-content: center;
  align-content: center;
  width: 300px;
  height: 300px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

44

align-content Property

Example:
(Center)



45

align-content Property


Example: (Flex-end)

```

.flex-container {
  display: -webkit-flex;
  display: flex;
  -webkit-flex-wrap: wrap;
  flex-wrap: wrap;
  -webkit-align-content: flex-end;
  align-content: flex-end;
  width: 300px;
  height: 300px;
  background-color: lightgrey;
}
<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design


46

align-content Property

Example: (Flex-end)



East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

47

Flex Item Properties - Ordering

The `order` property specifies the order of a flexible item relative to the rest of the flexible items inside the same container

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

48

Flex Item Properties - Ordering

Example:
(Ordering)

```

.flex-item {
  background-color: cornflowerblue;
  width: 100px;
  height: 100px;
  margin: 10px;
}

.first {
  -webkit-order: -1;
  order: -1;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item first">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

49

Item Properties - Ordering

Example:
(Ordering)



50

Flex Item Properties - Margin

Setting margin: auto; will absorb extra space
It can be used to push flex items into different positions

51

Flex Item Properties - Margin

Example:
(Margin)

```


.flex-item {
  background-color: cornflowerblue;
  width: 75px;
  height: 75px;
  margin: 10px;
}

.flex-item:first-child {
  margin-right: auto;
}

<div class="flex-container">
  <div class="flex-item">flex item 1</div>
  <div class="flex-item">flex item 2</div>
  <div class="flex-item">flex item 3</div>
</div>

```

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

52

Flex Item Properties - Margin

Example:
(Margin)



East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design

53

Flex Item Properties - Perfect Centering

Setting `margin: auto;` will make the item perfectly centered in both axis

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

54

Flex Item Properties - Margin

Example: (Margin)


```

.flex-item {
  background-color: cornflowerblue;
  width: 75px;
  height: 75px;
  margin: auto;
}

<div class="flex-container">
  <div class="flex-item">Perfect centering!</div>
</div>

```

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

55

Flex Item Properties - Margin

Example: (Margin)



East Tennessee State University
Department of Computing




CSCI 1720
Intermediate Web Design

56

Flex Item Properties - Align Self

The `align-self` property of flex items overrides the flex container's `align-items` property for that item. It has the same possible values as the `align-items` property.

East Tennessee State University
Department of Computing



CSCI 1720
Intermediate Web Design

57

Flex Item Properties - Align Self

Example: (Align self)

```

<div class="flex-container">
  <div class="flex-item item1">flex-start</div>
  <div class="flex-item item2">flex-end</div>
  <div class="flex-item item3">center</div>
  <div class="flex-item item4">baseline</div>
  <div class="flex-item item5">stretch</div>
</div>

```

```

.flex-item {
  background-color: cornflowerblue;
  width: 60px;
  min-height: 100px;
  margin: 10px;
}
.item1 {
  align-self: flex-start;
}
.item2 {
  align-self: flex-end;
}
.item3 {
  align-self: center;
}
.item4 {
  align-self: baseline;
}
.item5 {
  align-self: stretch;
}

```

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

58

Flex Item Properties - Align Self

Example: (Align self)

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

59

Flex Item Properties - Flex

The `flex` property specifies the length of the flex item, relative to the rest of the flex items inside the same container

East Tennessee State University
Department of Computing

CSCI 1720
Intermediate Web Design

60

Flex Item Properties - Flex

Example:
(Flex)

```

<div class="flex-container">
  <div class="flex-item item1">flex item 1</div>
  <div class="flex-item item2">flex item 2</div>
  <div class="flex-item item3">flex item 3</div>
</div>

```

```

.flex-item {
  background-color: cornflowerblue;
  margin: 10px;
}
.item1 {
  flex: 2;
}
.item2 {
  flex: 1;
}
.item3 {
  flex: 1;
}

```

East Tennessee State University
Department of Computing

CSCI 3720
Intermediate Web Design

61

Flex Item Properties - Flex

Example:
(Flex)

East Tennessee State University
Department of Computing

CSCI 3720
Intermediate Web Design

62

CSS3 Flexbox Properties

Property	Description
display	Specifies the type of box used for an HTML element
flex-direction	Specifies the direction of the flexible items inside a flex container
justify-content	Horizontally aligns the flex items when the items do not use all available space on the main-axis
align-items	Vertically aligns the flex items when the items do not use all available space on the cross-axis
flex-wrap	Specifies whether the flex items should wrap or not, if there is not enough room for them on one flex line
align-content	Modifies the behavior of the flex-wrap property. It is similar to align-items, but instead of aligning flex items, it aligns flex lines
flex-flow	A shorthand property for flex-direction and flex-wrap
order	Specifies the order of a flexible item relative to the rest of the flex items inside the same container
align-self	Used on flex items. Overrides the container's align-items property
flex	Specifies the length of a flex item, relative to the rest of the flex items inside the same container

East Tennessee State University
Department of Computing

CSCI 3720
Intermediate Web Design

63
